

고급 유량 교정기 (Advanced Mass Flow Multi-Meter)

용도(Applications)

- 정밀한 유량 측정 및 교정
- 양방향의 유량, 온도 및 차압 측정 및 저장
- Air, O₂, N₂, CO₂의 유량 측정
- CPAP, 의료용 양압기 유량 확인

특징(Features)

- 1ms 속도로 실시간 그래픽 기능 구현
- 4개의 측정값을 동시에 표시하는 컬러 터치 스크린
- 다양한 튜브에 연결 가능하여 활용성 증대
- 데이터 저장 및 전용 소프트웨어 제공



Advance Model : 5210/ 5310

Model		Air, N ₂	Air, O ₂ , N ₂	Air, CO ₂ , N ₂	O ₂	CO ₂
Low-Flow	±30 L/min	5210-1	5210-2	5210-3	5210-6	5210-7
High-Flow	±300 L/min	5310-1	5310-2	5310-3	5310-4	5310-5

SPECIFICATIONS

Model	5210	5310
Flow Range	±30 L/min	±300 L/min
Flow Accuracy	2% of Reading or 0.005 L/min	2% of Reading or 0.05 L/min
Volume Range	0.002 ~ 99 L	0.004 ~ 99 L
Volume Accuracy	2% of reading or 1 mL	2% of reading or 1 mL
Tube Adapters	3/8 inch, 1/4 inch, 10mm	22mm ISO, 1/2 inch
Tube Options	-	3/4 inch, 3/8 inch NPT, 15mm ISO
Temperature Sensor	Range -10 to 50°C, ±1°C	
Display	2.8 inch Color LCD Touchscreen	
Internal Storage	1 GB storage, max 20 datalog files	
Digital Output	USB, RS-232 Serial using an optional USB-A to RS232 converter cable	
Power	5.0 VDC ±5%, 500 mA maximum, Supplied through USB-C port	
Dimensions (L x W x H)	18.1cm x 6.9cm x 5.0cm / Polycarbonate	
Weight	230g, including protective end caps	

