

NO, NO2 측정기 (Handheld NO, NO2 Monitor)

용도(Applications)

- 실내 및 작업 환경의 NO, NO2 측정
- 온도, 습도, 기압, 습구 온도, 이슬점 측정
- NO, NO₂ 이외에 CO₂ 추가 선택 가능

특징(Features)

- 가볍고 튼튼한 초소형 디자인
- 실시간 측정, 측정값 및 그래프 저장 기능
- 대용량 메모리로 장시간 측정값 저장 기능
- 무선프린터와 프로브 선택 가능



Model : SI-AQ PRO

SPECIFICATIONS

Parameter	Sensor	Range	Resolution	Accuracy
NO	Electrochemical ¹	0 ~ 250 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
NO ₂	Electrochemical ¹	0 ~ 20 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
CO ₂	NDIR ¹	0 ~ 5,000 ppm	1 ppm	±2% rdg ±10 ppm
Relative Humidity	Capacitive	5 ~ 95%	0.1%	±2% RH
Ambient Temp.	Pt100	-40 ~ 125°C	0.1°C	± 0.4°C (0~60°C)
Barometric Pressure	Piezoresistive	260 ~ 1,260 mbar	1 mbar	± 2 mbar
Differential Pressure*	Piezoresistive	-100 mbar to 100 mbar (-40 inH2O to 40 inH2O)	0.1 mbar (0.1 inH2O)	±1% rdg
Temperature Type K T1	Tc K	0 ~ 1,100°C	1°C	3°C or 2% rdg
Air Velocity	Calculated	0 - 91 m/s (0 ~ 300 ft/sec)	1 m/s (1 ft/sec)	
Electromagnetic Compatibility		EN 61326-1, Portable Equipment		
Size / Weight		200 x 190 x 9 mm (H x W x D) / 3.6 kg		

1. Other Ranges are Available Upon Request 2. Accuracy Based on Laboratory Conditions

* Requires connection accessories, flexible tubes and connections available as option in the Si-AQ Kit Press. Diff.


* Accessories




Bluetooth® Printer
(Si-AQ Bluetooth® Printer)



Sampling Probe
(Si-AQ Probe with Hose)



Moisture Exchange
Tube for Calibration
(Si-AQ Moisture Exchange)



Pitot Tube for Air Velocity
(Si-AQ Pitot Tube)